

REVO Residential Energy Storage Inverters

Split-Phase hybrid inverter

Battery low voltage



KEY STRENGTHS

- Support the construction of three-phase systems.
- Capable of supporting 100% unbalanced loads.
- Support 4-channel MPPT
- 100A pass through.
- AC solar to retrofit existing solar system(on-grid & off-grid).
- Grid & generator separately connected, support storing energy from diesel generator.

Model	R5KLNA	R6KLNA	R7K6LNA	R8KLNA	R10KLNA
PV input data					
Max. PV input power (kW)	7.5	9	12	12	15
Max. PV input voltage (V)			500		
Min. PV input voltage (V)			120		
Start-up voltage (V)			120		
MPPT voltage range (without battery)(V)			120~500		
MPPT voltage range@full-load (V)			150~430		
Rated PV input voltage (V)			310		
No. of MPPT trackers			4		
No. of strings per MPPT tracker			1/1/1/1		
Max. input current per MPPT (A)			14/14/14/14		
Max. short-circuit current per MPPT (A)			22/22/22/22		

Battery input data

Battery type	Lithium-ion / Lead-acid				
Max. charge / discharge power (kW)	5	6	7.6	8	10
Battery voltage range (V)	40~60				
Rated battery voltage (V)	48				
Max. charging / discharging current (A)	120/120	135/135	190/190	190/190	190/210
Rated charge / discharge current (A)	120/120	135/135	190/190	190/190	190/210
Charging strategy for Li-Ion battery	Self-adaption to BMS				
BMS communication	CAN				

AC output data (grid side)

Rated output power (kW)	5	6	7.6	8	10
Max. apparent output power (kVA)	5.5	6.6	8.4	8.8	11
Rated grid voltage (V)	110-127/208-240V split phase, 240V single phase				
Grid voltage range (V)	192~288				
Rated grid frequency (Hz)	60				
Grid frequency range(Hz)	55 to 65				
Rated output current (A)	20.8	25	31.7	33.3	41.7
Max. AC output current (A)	22.9	27.5	34.8	36.7	45.8
Power factor	0.8leading~0.8lagging				
Max. grid passthrough current(A)	100				
THDi	<3%				
Grid type	2L+N+PE				

AC output data (load side)

Rated output power (kW)	5	6	7.6	8	10
Max. apparent output power (kVA)	5.5	6.6	8.4	8.8	11
Rated output voltage (L-N/L1-L2) (V)	120/240				
Rated output frequency (Hz)	60				
Rated output current (A)	20.8	25	31.7	33.3	41.7
Max. AC output current (A)	22.9	27.5	34.8	36.7	45.8
Peak output power	110%,30s / 120%,10s / 150%,0.02s				
Back-up switch time (ms)	<20				
THDu	<2%				

Protection

Supported protection	Arc fault protection, PV reverse polarity protection, Anti-islanding protection, Ground fault protection Leakage current protection, Insulation resistance detection, Backup output short circuit protection, AC under-voltage protection, AC output over-current protection, AC over-voltage protection,
Surge protection	DC Type II / AC Type II
Over voltage category	DC Type II / AC Type III

Certifications and standards

Certificates	FCC Part 15 Class B; UL1741SA all options, UL1699B, CSA 22.2; IEEE1547
--------------	--

General data

Ingress protection	IP65 / NEMA 3R
Operating temperature range (°C)	-25~+60
Cooling	FAN cooling
Relative humidity	0-95%
Operating altitude (m)	0~4,000(Derating above 2,000 altitude)
Dimensions W*D*H (mm)	450 x 820 x 240
Weight (kg)	47
Topology (solar / battery)	Transformerless / Transformer
Noise emission (dB)	48

Display and communication

Display	Touch panel
Communication	RS485, 4G(optional), Wi-Fi